YARDBIRD & SUPER DUTY YARDBIRD DUMP BODIES











Durability in a Light Duty Package.

Backed by over 100 years of experience, the DuraClass Yardbird and Super Duty Yardbird are the premium Light Duty choices for contractors and municipalities who don't want to compromise on quality and durability. The Yardbird and Super Duty Yardbird feature our patented DuraClass design, with a continuous formed body sidewall and fully enclosed top rail for superior resistance to moisture and corrosion.

The double-wall body side, full depth rear corner posts and enclosed front corner posts, plus our famous interlaced understructure give Yardbirds uncommon strength and rigidity for a light duty dump body. Yardbirds come standard with quick release upper tailgate pins, ¼ cabshield with window, and fully welded construction. Choose from additional options including crossmemberless understructure, drop sides, and stainless steel construction.

The 1520 Hoist, standard on all DuraClass Yardbirds, is equipped with a powerful 5-inch chrome cylinder, heavy-duty platform hinge, and your choice of double-acting electric or direct mount hydraulics. The 1520's rugged, high-quality frame design and premium components will provide a long hoist life. Enjoy simple maintenance with greaseable fittings on all bearing points and a removeable cylinder head.

NEW FEATURES

- 1" diameter tailgate pin
- %" GR43 tailgate chains
- Chain brackets are banjo eye plates
- Pipe handle

AVAILABLE OPTIONS

- Drop Sides
- Crossmemberless Understructure
- · LED Marker Light Kit
- Standard LED STT Light Kit
- ½ Cabshield
- Stainless Steel

YARDBIRD SPECIFICATIONS		
Inside Length	8' 1"	10'
Width	6' 8"	6' 8"
Material	10 gauge	10 gauge
Body Capacity (yards)	2 - 3	2 - 3
Side / Front / Rear Height (inches)	14 / 20 / 20	12 / 18 / 18
Weight, including hoist (lbs)	1700	2002

SUPER DUTY YARDBIRD SPECIFICATIONS									
Inside Length	8' 1"	9'	9'	10'	11'	11'			
Width	7'	7 ¹	7 ¹	7'	7'	7'			
Material	10 gauge	10 gauge	10 gauge	10 gauge	10 gauge	10 gauge			
Body Capacity (yards)	3 - 4	2.5 - 3.5	3.5 - 4.5	3 - 4	2.5 - 3.5	3.5 - 4.5			
Side / Front / Rear Height (inches)	18 / 24 / 24	14 / 20 / 20	18 / 24 / 24	14 / 20 / 20	12 / 18 / 18	14 / 20 / 20			
Weight, including hoist (lbs)	1999	1831	2101	2090	2122	2182			

1520 FLM HOIST CAPACITY* (TONS)							
Body Length	8'	9'	10'	11'	12'		
Rear Overhang	6"	6"	6"	6"	6"		
Capacity*	13.5	11.6	10.3	9.3	8.4		

1520 FLM HOIST SPECIFICATIONS

- NTEA Class: 30
- Cylinder Bore: 5"
- Cylinder Stroke: 20"
- GPM (at 1000 RPM): 4
- Weight: 635 lbs (less oil & PTO)
- Mounting Height: 12 3/4"

*Capacity is based on water-level load and approximately 50° dump angle.

All bodies shown with some optional equipment. Models and options are subject to change without notice.



P.O. Box 49 1425 Highway 25 North Tishomingo, MS 38873 800.255.4345 Fax: 800.728.4345 www.duraclass.com

CONTACT YOUR DISTRIBUTOR