

### Specifications

#### STANDARD CONSTRUCTION

- Bulkhead (non-ribbed) ..... 14 ga. galvalneal steel
- Compartment Bottoms ..... 16 ga. galvalneal steel
- Compartment Tops ..... 14 ga. galvalneal steel (one-piece integral with loadspace centers)
- Crossmember-front ..... 7 ga. hot-rolled formed channels
- Crossmember-intermediate 12 ga. galvalneal steel
- Crossmember-rear ..... 7 ga. hot-rolled formed channels
- Doors ..... 20 ga. galvalneal steel double panel
- End panels-front ..... 14 ga. galvalneal steel
- End panels-rear ..... 14 ga. galvalneal steel
- Fender panels ..... 16 ga. galvalneal steel
- Floor ..... 12 ga. embossed galvalneal treadplate
- Intermediate panels ..... 16 ga. galvalneal steel
- Loadspace inside centers ... 14 ga. galvalneal steel (one-piece integral with compartment tops)
- Longitudinals ..... 10 ga. galvalneal formed
- Shelving ..... 14 ga. high-spangle galvanized (250# static load capacity)
- Tailgate ..... 18 ga. galvalneal (double panel, formed construction)
- A-40 galvalneal construction. Two-sided zinc coated galvalneal (.40 oz zinc coating per square foot of steel) provides maximum rust and corrosion resistance.
- Body sides are constructed using plated lock-bolt fasteners.
- Floor understructure rigidly welded for structural integrity and durability. Mounting points re-inforced w/U-channel gussets.



Shown with optional  
recessed lighted bumper

#### STANDARD FEATURES / EQUIPMENT

- **Construction** - Lock-bolt to provide unbeatable durability, eliminates rust-causing welding and grinding, and promotes corrosion-free, long-lasting product. Floor understructure rigidly welded for structural integrity and undercoated for superior rust protection.
- **Compartment Tops** – Smooth seamless surface to enhance appearance.
- **Cutouts** – Openings in intermediate panels between horizontal and adjacent vertical compartments provides extended storage between compartments.
- **Door Hinges** - Concealed, bolt-on style provides increased security and clean appearance
- **Door Latches** - Bolt-on rotary style with stainless steel paddle handles and stainless steel pans.
- **Lock Cylinders** are keyed alike with double-bitted keys and are power door lock ready for easy after-market installation.
- **Door Striker** - Adjustable, bolt-on.
- **Vertical Doors** - Spring-loaded door holders to hold doors in the fully open position and assist in closing.
- **Horizontal Doors** – Use vinyl coated aircraft quality cables for support in open position.
- **Automotive Style Door Seal** - STAHL-engineered clip-on to allow easy removal for painting, replacement and quicker installation. Door seals against a flat surface for extra protection against water leakage.
- **Drip Rail** - Concealed to provide extra protection against water leakage.
- **Fender Panels** - Bolt-on die-stamped with radius wheel opening.
- **Tailgate** – Two point slam-locking featuring anti-rack/rattle hardware.
- **Shelving** – Bolt-in material trays with dividers.
- **Powder Coat Finish** – Body exterior, compartment interiors, and cargo area surfaces are finished in a durable, corrosion resistant white powder coat.
- **Undercoating** - On bottom of floor and wheelwells.
- **STAHL** 's exclusive 5-year "No Rust, No Bust" warranty.

Continues on reverse side...

## STANDARD SHELVING PACKAGE

COMPARTMENT	BODY LENGTH	COMPT. WIDTH	CURBSIDE COMPARTMENTATION	STREETSIDE COMPARTMENTATION
Front vertical	98" 110" 134"	29.81" 33.44" 33.44"	(2) adjustable trays with dividers	(2) adjustable trays with dividers
Second vertical	134"	24.00"	(2) adjustable trays with dividers	(2) adjustable trays with dividers
Horizontal	ALL	47.19"	(1) adjustable tray with dividers	Open
Rear vertical	98" 110" 134"	21.00" 29.81" 29.81"	(1) adjustable tray with dividers	(1) adjustable tray with dividers

## DIMENSIONAL SPECIFICATIONS

DESCRIPTION	98VVS	98VVS LT	98VVD	110VVS	110VVD	110VVD	134VVD	134VVD
Overall Body Length	98"	98"	98"	110"	110"	110"	134"	134"
Loadspace Floor Width	48.50"	48.50"	52.50"	48.50"	48.50"	52.50"	48.50"	52.50"
Overall Body Width	79.98"	79.98"	96.00"	79.98"	92.00"	96.00"	92.00"	96.00"
Cab-to-axle	56.00"	56.00"	56.00"	60.00"	60.00"	60.00"	84.00"	84.00"
Front Vertical Width	29.81"	29.81"	29.81"	33.44"	33.44"	33.44"	33.44"	33.44"
Clear door opening	25.31"	25.31"	25.31"	28.94"	28.94"	28.94"	28.94"	28.94"
Second Vertical Width	n/a	n/a	n/a	n/a	n/a	n/a	24.00"	24.00"
Clear door opening	n/a	n/a	n/a	n/a	n/a	n/a	19.69"	19.69"
Horizontal Width	47.19"							
Clear door opening	45.31"							
Rear Vertical Width	21.00"	21.00"	21.00"	29.81"	29.81"	29.81"	29.81"	29.81"
Clear door opening	16.75"	16.75"	16.75"	25.56"	25.56"	25.56"	25.56"	25.56"
Vertical Compartment Height	39.50"	36.00"	39.50"					
Clear door opening	36.37"	31.13" *	36.37"					
Horizontal Compartment Height	18.07"	11.19" *	18.07"	18.07"	18.07"	18.07"	18.07"	18.07"
Clear door opening	14.94"	9.69" *	14.94"	14.94"	14.94"	14.94"	14.94"	14.94"
Side Compartment Depth (useable – above offset)	13.63"	13.63"	19.63"	13.63"	19.63"	19.63"	19.63"	19.63"
Floor-to-Compartment Top Height	25.50"	22.00"	25.50"	25.50"	25.50"	25.50"	25.50"	25.50"
Tailgate Height Above Floor	9.10"							
Tailgate Height Overall	11.22"							

\* Note: Top Pak clear door openings are from the bottom of the Top Pak pan.

### OPTIONAL EQUIPMENT

- Back Up Alarms
- Bar Lock Master Locking System
- Bumpers
- Crane Reinforcement (2,000-4,000#)
- Dome Lights
- Drawers
- Folding Steps & Grab Handles
- Fuel Fill (Alum.)
- Primer Paint
- High Roof
- Hitches
- Hooks
- Ladder Rack
- Light Kit – LED
- Louvers
- Low Sliding Roof
- Off-Road Mounting Kit
- Shelves
- Paint and Installation
- Pipe Carrier
- Power Door Locks
- Tank Compartment
- Tie-Down Ring
- Tire Carrier
- Top Pak (add-on)
- Trays
- Treadbrite Overlay

Due to constant product evaluations and improvements, specifications are subject to change without notice.

